


METAL FIREMAN'S POLE

PDS_341.001



- **341.001.001.001** metal fireman's pole - free end - red
- **341.001.002.001** metal fireman's pole - free end - green

	pcs	pcs	pcs	pcs	pcs	pcs	pcs
341.001.	6,60 kg	× 1	250 × 60 × 4 cm	6,60 kg	1 × 50 = 50	360 × 110 × 36 cm	355 kg

CLIMBING



REVISION: 18/10/2023



METAL FIREMAN'S POLE

- powder coated
- bore holes diameter 11 mm in fixation plates
- exterior tube diameter 38 mm (wall thickness 2 mm)
- to be placed in concrete
- bolts not included

METALLRUTSCHSTANGE

- pulverbeschichtet
- Durchmesser der Bohrlöcher in den Befestigungsplatten 11 mm
- Außendurchmesser Rohr 38 mm (Wandstärke 2 mm)
- im Beton befestigen
- Schrauben werden nicht mitgeliefert

METALEN GLIJPAAL

- gepoedercoat
- schroefgaten in bevestigingsplaatjes diameter 11 mm
- buitendiameter buis 38 mm (wanddikte 2 mm)
- te plaatsen in beton
- bouten niet meegeleverd

TUBO BAJADA BOMBEROS

- termolacada por espolvoreado
- agujeros en las placas de fijación diámetro 11 mm
- diámetro exterior del tubo 38 mm (espesor del material 2 mm)
- a fijar en hormigón
- viene sin pernos

POTEAU À GLISSER

- thermolaqué par poudrage
- trous diamètre 11 mm dans les plaques de fixation
- diamètre extérieur du tube 38 mm (épaisseur paroi 2 mm)
- à fixer dans le béton
- fourni sans les boulons
- 0

RURA STRAŻACKA

- malowana proszkowo
- otwory o śr. 11 mm w płaskowniku montażowym
- średnica rury zewnętrznej 38 mm (gr. ścianki 2 mm)
- do osadzenia w betonie
- zestaw nie zawiera śrub

MANUAL
M341

STATUS
STD

DIMENSIONS
2500 × 600 × 118 mm

CLIMBING



KBT nv
Hemelrijken 12
2890 Puurs-Sint-Amands
Belgium

KBT Polska sp. z o.o.
ul. M. Konopnickiej 6
00-491 Warszawa
Poland